

AUTHORIZATION TO MARK

This authorizes the application of the Certification Mark(s) shown below to the models described in the Product(s) Covered section when made in accordance with the conditions set forth in the Certification Agreement and Listing Report. This authorization also applies to multiple listee model(s) identified on the correlation page of the Listing Report.

This document is the property of Intertek Testing Services and is not transferable. The certification mark(s) may

Applicant: Westlock Controls Corporation
Address: 280 N. Midland Ave. Ste. 258
Saddle Brook, NJ. 07663
Country: USA

Manufacturer: Westlock Controls Corporation
Address: 280 N. Midland Ave. Ste. 258
Saddle Brook, NJ. 07663
Country: USA

Party Authorized To Apply Mark: Same as Manufacturer
Report Issuing Office: Intertek Testing Services NA, Inc., Cortland, NY

Control Number: 5013405

Authorized by: 
for L. Matthew Snyder, Certification Manager



This document supersedes all previous Authorizations to Mark for the noted Report Number.

This Authorization to Mark is for the exclusive use of Intertek's Client and is provided pursuant to the Certification agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this Authorization to Mark. Only the Client is authorized to permit copying or distribution of this Authorization to Mark and then only in its entirety. Use of Intertek's Certification mark is restricted to the conditions laid out in the agreement and in this Authorization to Mark. Any further use of the Intertek name for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. Initial Factory Assessments and Follow up Services are for the purpose of assuring appropriate usage of the Certification mark in accordance with the agreement, they are not for the purposes of production quality control and do not relieve the Client of their obligations in this respect.

Intertek Testing Services NA Inc.
545 East Algonquin Road, Arlington Heights, IL 60005
Telephone 800-345-3851 or 847-439-5667 Fax 312-283-1672

Standard(s):	<p>Explosion-Proof and Dust-Ignition-Proof Electrical Equipment for Use in Hazardous (Classified) Locations [UL 1203:2013 Ed.5+R:05Apr2022]</p> <p>Enclosures for use in Class II, Division 1, Groups E, F, and G Hazardous Locations [CSA C22.2#25:2017 Ed.4]</p> <p>Explosion-proof Enclosures for Use in Class I Hazardous Locations (R2016) [CSA C22.2#30:1986 Ed.3+G1;G2]</p> <p>Explosive Atmospheres – Part 0: Equipment – General Requirements [UL 60079-0:2019 Ed.7]</p> <p>Explosive Atmospheres — Part 0: Equipment — General Requirements [CSA C22.2#60079-0:2019 Ed.4]</p> <p>Standard for Safety Explosive Atmospheres - Part 1: Equipment Protection by Flameproof Enclosures "d" [UL 60079-1:2015 Ed.7+R:23Jan2020]</p> <p>Explosive Atmospheres - Part 1: Equipment Protection by Flameproof Enclosures "d" [CSA C22.2#60079-1:2016 Ed.3]</p> <p>Explosive Atmospheres - Part 31: Equipment Dust Ignition Protection by Enclosure "t" [UL 60079-31:2015 Ed.2]</p> <p>Explosive Atmospheres - Part 31: Equipment Dust Ignition Protection By Enclosure "T" [CSA C22.2#60079-31:2015 Ed.2]</p>
Product:	<p>Valve Position Monitor For Use In: Class I, Division 1 Groups C and D; Class II, Division 1, Groups E, F, and G, T*; Class I, Zone 1, AEx db / Ex db IIB+H2 T* Gb; Zone 21, AEx tb / Ex tb IIIC T* Db IP6X; Non-Incendive (for model 9479 Series and D281/D291 Series with sensors options xM6, xM08 and xM12 only) for Class I, Division 2, Groups A, B, C and D, T*, T2C (Heater Option Only); Type 4, 4X, IP66/67</p>

2200 followed by 4, 6; followed by 3, 5, 6, 7, 9, 0; followed by A, S; followed by two characters; Followed by one character; followed by 0, A, E; followed by 0, C, G, H, J; followed by one characters, followed by 1 to 4; followed by 2, 3; followed by three characters; may be followed by A; may be followed by up to two numbers.

2007 followed by one character; followed by two characters; followed by 2A, 2B, 2E, 4A, 4B, 4E, 4F, EA, 2M, 4M, 2S, 4S; followed by 0000, up to 6M02, up to 4M04, up to 4M03; followed by 00, DS; may be followed by five characters.

E2007 followed by one character; followed by two characters; followed by 2E, 4E, EM; followed by up to 6M02, up to 2M04, up to 2M03; followed by 00, DS; followed by DT, DZ, DY, ET, EZ, EY; followed by O, L, followed by three characters, followed by d, may be followed by five characters.

Models:

9479 followed by one character; followed by two characters; followed by 2A, 2B, 2E, 4A, 4B, 4E, 4F, EA, 2M, 4M, 2S, 4S; followed by up to 6M06, up to 6M08, up to 6M10, up to 6M12, 2M13, up to 4M17, up to 4M18, up to 6M14, up to 4MA5, up to 6MAO, up to 6MAP, up to 4MAV, 2MEA, up to 4MEB, up to 4MEH, 2MEM, up to 6MEO, up to 6MEP, up to 4MEQ, up to 6MES, up to 6MEU, up to 4MEX; followed by 00, DS; may be followed by five characters.

E9479 followed by one character, followed by two characters; followed by 2E, 4E, EM; followed by up to 6M06, up to 6M08, up to 6M12, 2M13, 2M17, 2M18, up to 6M14, up to 4MA5, up to 6MAO, up to 6MAP, up to 4MAV, 2MEA, up to 4MEB, up to 4MEH, 2MEM, up to 6MEO, up to 6MEP, up to 4MEQ, up to 6MES, up to 6MEU, up to 4MEX ; followed by 00, DS; followed by DT, DZ, DY, ET, EZ, EY; followed by O, L, followed by three characters, followed by one character, followed by five characters.

D280, D290 followed by NP, NT, SP, ST; followed by up to 2M04, up to 4M06, up to 4M08, up to 4M09, up to 4M12; followed by two characters; followed by 0, T, Z; followed by three characters; followed by one character; followed by EX; followed by 2, 3.

D281, D291 followed by NP, NT, SP, ST; followed by 0000, up to 2M04, up to 4M06, up to 4M08, up to 4M09, up to 4M12; followed by two characters; followed by EX; followed by 2, 3.